

TECHNICAL DAT SHEET

ENDURA Penetrating Grease

DESCRIPTION: Endura is a high strength lubricant with exceptional adhesive strength. It sprays as a liquid, penetrates tight areas and sets up as a long lasting grease. PTFE is added, giving Endura greater lubricity and heat resistance. This exclusive formula assures that the product will penetrate and stay where it is sprayed, resist throw off, squeeze out, high pressure and water. Endura provides protection against rust, corrosion acids, alkalis and has a temperature range of -30°F to over 600°F. Endura is also salt resistant.

USES: *Open Gears *Door Hinges *Chains and Sprockets *Marine applications *Rubbish Companies *Fleet Truck *Lawn Equipment *Farm Equipment

DIRECTIONS: 1. Spray area to be treated long enough to saturate.
2. Allow to penetrate.

PACKAGING: 16 oz aerosol 12/case

STORAGE: Store below 120°F.

SPECIFICATIONS:

| | | | |
|------------------|-------|---------------|---------|
| Color | clear | Odor | solvent |
| Specific Gravity | 0.7 | Density | 4.0 |
| Flash Point | -40°F | Freeze Stable | yes |
| Effect on Paint | none | | |

STORAGE: Store below 120°F.

PRODUCT #: C1630